

## TECHNICAL SPECIFICATION: ANTIOLIO (OIL REPELLENT)

Transparent solvent-based water- and oil-repellent treatment for internal and external concrete surfaces

In the presence of a mature and untreated concrete floor (e.g. in Pavilux<sup>®</sup>, Deco Nuvolato<sup>®</sup>, stamped floor, or Italianterrazzo Isoplam<sup>®</sup>) wash with Isoplam<sup>®</sup>'s **Plam Super Cleaner** degreaser or with Isoplam<sup>®</sup>'s acid **Plam Apripori** with Isoplam<sup>®</sup> **Black Disc** mounted on the Isoplam<sup>®</sup> **Monobrush**. Thoroughly rinse after.

After complete drying, apply 2 coats of Isoplam<sup>®</sup> **Antiolio Oil Repellent**, at a rate of approx. 0.15 L/m<sup>2</sup> per coat, with an Isoplam<sup>®</sup> roller or airless.

The price includes: the protection of parts not affected by the processing, the supply and transportation of materials to the construction site, the equipment and machinery for carrying out the work.

For a total of ..... m<sup>2</sup> at the price of € ...../m<sup>2</sup>

### Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy  
Tel: +39 0423 925023 - Mail: info@isoplam.it  
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.  
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996  
Società soggetta all'attività di direzione e coordinamento di MDF Holding