

TECHNICAL SPECIFICATION: DECO NUVOLATO GRIP

Carry on of continuous external concrete flooring with Isoplam® anti-slip “cloudy” finish

Preparation of the surface with the laying of Isoplam® **Nylon**, Isoplam® **Nonwoven Fabric**, Isoplam® **Insulating Strip**, Isoplam® mesh **Spacers** and suitable mesh and laying of continuous monolithic floor in cls with a minimum thickness of 8 cm, according to UNI EN 206 1 and UNI 11146, added with **Coldpav** Isoplam® gripping accelerator or **Hotpav** Isoplam® gripping retarder at a rate of about 1.2 L per 100 kg of concrete and with Isoplam® **Polypropylene Fibers** at a rate of about 0.6 Kg/m³ of cls.

Manual drafting of the CLS with Isoplam® **Aluminium Screed** or mechanised with Isoplam® **Vibrating Screed**.

Roughing of fresh concrete with the aid of Isoplam® **Power Trowel** with Isoplam® **Power trowel Blades** or mounted **Pans**.

Dusting of **Deco Nuvolato** Isoplam® at a rate of about 4 Kg/m² according to the colour chosen by the Works Management based on the Isoplam® **Colour Chart**.

Working of the surface with Isoplam® **Combined power trowel blades** mounted on the Isoplam® **Power Trowel** and with the help of Isoplam® **E Red** as needed to better incorporate the Deco Nuvolato until an anti-slip finish is obtained. Application of Isoplam® **Anti-evaporation** treatment in a ratio of about 0.2 L/m² to protect the floor from rapid drying. Execution of the control joints with Isoplam® **Diamond disc** and laying of Isoplam® expanded polyethylene cord **Backer Rod**.

After drying the cls, apply Isoplam® **Plam Sigil** or Isoplam® **Colored Silicone**.

Floor washing and application of Isoplam® protection: consult the Isoplam® Technical Department for the choice of the most suitable product.

The price includes: the protection of parts not affected by the processing, the supply and transportation of materials to the construction site, the equipment and machinery for carrying out the work.

For a total of m² at the price of €/m²

Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy
Tel: +39 0423 925023 - Mail: info@isoplam.it
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996
Società soggetta all'attività di direzione e coordinamento di MDF Holding