

## TECHNICAL SPECIFICATION: TERRAZZOVERLAY™ XL

Implementation of a polished (2-5 cm) internal/external coating with Venetian effect.

Thorough cleaning of suitable existing support.

Installation of Isoplam® sandable **Plam profil** profiles or marble elements to create control joints, bringing existing ones on the screed to the surface.

Application of **Deco Epox W Bi** Isoplam® as an absorption leveling agent for the support.

Application of **Skyprimer** Isoplam® (at a rate of approximately 1 kg/m<sup>2</sup>) two-component epoxy to be dusted with **Quartz 0.6-1.2** Isoplam® (at a rate of approximately 3 Kg/m<sup>2</sup>) washed and dried.

Spread, in a thickness of approximately 3 cm, the mixture of **Deco Ghiaino** Isoplam® (2.5 Kg/m<sup>2</sup>/cm thick) + Cement (5 Kg/m<sup>2</sup>/cm thick) + **Deco Bind** (2 Lt/m<sup>2</sup>/ cm thick) + water (0.5 Lt/m<sup>2</sup>/cm thick) + **Marble grit** (12.5 Kg/m<sup>2</sup>/cm thick), chosen by the Works Management according to the Isoplam® Color Chart and the Isoplam Granules Deck ® and worked with Staggia Isoplam®.

Surface smoothing with Isoplam® steel board

Homogenization of the surface with Isoplam® stencil roller and spreading of moistened Isoplam® non-woven fabric and Isoplam® Nylon to allow the correct curing of the covering.

Sanding the surface with an Isoplam® sander, passing Isoplam® abrasive discs, and filling any small holes.

Polishing of the surface with Isoplam® polishing discs for a shiny indoor effect or brushing with Isoplam® brush discs for an outdoor non-slip effect.

Application of Isoplam® protective: consult the Isoplam® Technical Office to choose the most suitable product.

The price includes: the protection of the parts not affected by the work, the supply and transport of materials to the construction site, the equipment and machinery for carrying out the work.

**For a total of ... m<sup>2</sup> at a cost of € .../m<sup>2</sup> + VAT.**

### Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy  
Tel: +39 0423 925023 - Mail: [info@isoplam.it](mailto:info@isoplam.it)  
Pec: [isoplamsrl@pec.it](mailto:isoplamsrl@pec.it) - Web: [www.isoplam.it](http://www.isoplam.it)

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.  
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996  
Società soggetta all'attività di direzione e coordinamento di MDF Holding