

PVC SPACER

for welded mesh

DESCRIPTION

The Isoplam linear spacer is a disposable plastic bar that remains embedded in the concrete used for industrial, cloudy, stamped and cementitious screeds. Plastic spacers are essential for the correct positioning of the electro-welded reinforcement mesh of the concrete floor and guarantee compliance with the concrete cover before and during concrete casting. The plastic spacer has an inverted U-profile, is very robust and compression-resistant and is easy to use. The presence of holes on three sides of the spacer profile allows ideal penetration of the concrete. They are available in various heights depending on the thickness of the concrete: the correct position of the mesh reduces the risk of cracks and cracks on the surface of the flooring. They are made of PP Polypropylene HD which guarantees high strength and are therefore able to withstand high loads.

FIELDS OF USE

Plastic spacers for electro-welded mesh are used in industrial, stamped concrete floors and cementitious screeds. They can also be used upside down for use in insulating panels, floors and prefabricated structures.

HOW TO USE

The spacers must be positioned parallel to each other at a distance of no more than one meter from each other.

TECHNICAL AND PERFORMANCE DATA

Appearance	Shaped bar with a length of 2 m and variable height
Material	HD polypropylene
Color	Grey
Weight capacity	3000 kg per piece evenly distributed