

TECHNICAL SPECIFICATION: OXYDECOR[®] VERDERAME ANTICO

Carry out of a decorative coating that recreates the appearance of ancient verderame

Cleaning of the substrate and application of **Deco Primer Finish** Isoplam[®] with a roller or brush at a rate of approx. 0.10 L/m².

Application of the **Oxygreen Primer** Isoplam[®] colored primer with a roller at a rate of approx. 0.10 L/m².

Uneven application of **Oxygreen Powder** Isoplam[®] + **Oxygreen Liquid** Isoplam[®] with a roller, brush or Isoplam[®] plastic trowel at a rate of approx. 0.25 L/m².

Uneven application of the **Oxygreen Oxidant + Oxygreen Activator** Isoplam[®] mixture at a rate of 0.17 L/m² and let dry for a couple of days.

Uneven application of **Oxyrust Paint** Isoplam[®] with Isoplam[®] plastic trowel at a rate of approx. 0.22 L/m².

Irregular nebulization of **Oxyrust Oxidant** Isoplam[®] at a rate of approx. 0.10 L/m² and, subsequently, of **Oxyrust Activator** Isoplam[®] at a rate of approx. 0.12 L/m², uniformly over the entire surface, with an Isoplam[®] Acid Pump, in order to block the oxidation cycle.

Application, by roller or spray, of the water-based protector **Oxygreen Protection** Isoplam[®] at a rate of approx. 0.14 L/m² or of the polyurethane protective resin **Plam Pol Water** matt Isoplam[®] at a rate of approx. 0.20 L/m².

The price includes: coverage of the parts not affected by the processing, the supply and transport of materials to the construction site, the equipment and any machinery for carrying out the processing.

For a total of m² at the price of €/m²

Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy
Tel: +39 0423 925023 - Mail: info@isoplam.it
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996
Società soggetta all'attività di direzione e coordinamento di MDF Holding