

TECHNICAL SPECIFICATION: OXYDECOR[®] VERDERAME

Carry out of a decorative coating that recreates the appearance of verderame

Cleaning of the surface and application with roller or brush of **Deco Primer Finish** Isoplam[®] in a ratio of about 0.10 L/m².

Roller application of Isoplam[®] coloured primer **Oxygreen Primer** in a ratio of about 0.10 L/m².

Uniform application of two coats of **Oxygreen Powder Isoplam[®] + Oxygreen Liquid Isoplam[®]** with a roller, brush or Isoplam[®] plastic trowel at a rate of approx. 0.25 L/m².

Irregular spraying of Isoplam[®] **Oxygreen Oxidant** + Isoplam[®] **Oxyrust Activator** at a rate of about 0.17 L/m with an Isoplam[®] **Acid Pump**.

Roller or spray application of Isoplam[®] water-based **Oxygreen Protection** at a rate of about 0.14 L/m² or Isoplam[®] matt polyurethane protective resin **Plam Pol Water** at a rate of about 0.20 L/m².

The price includes: the protection of parts not affected by the processing, the supply and transportation of materials to the construction site, the equipment and machinery for carrying out the work.

For a total of m² at the price of €/m²

Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy
Tel: +39 0423 925023 - Mail: info@isoplam.it
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996
Società soggetta all'attività di direzione e coordinamento di MDF Holding