

SPECIFICATIONS PAVILUX SABLEE

Execution of a low-thickness polished Isoplam[®] cementitious flooring system.

Careful cleaning and mechanical roughening of the existing substrate in cured concrete, executed in compliance with UNI EN 206-1.

Application of Isoplam[®] **Cement Primer** bonding primer using **Isoplam[®] Broom**, or alternatively Isoplam[®] **Skyprimer** applied with a trowel and broadcast with **Isoplam[®] Quartz**.

Installation, to a thickness of approx. 2–3 cm, of the Isoplam[®] **Pavilux Overlay** Cemento mixture, at a rate of approx. 20 kg/m² per cm of thickness, followed by leveling using Isoplam[®] **Screed Bar**.

Manual rough finishing of the fresh material using an Isoplam[®] **magnesium float** or by means of an Isoplam[®] mechanical power trowel.

Broadcast application of Isoplam[®] **Plam Hardening** surface hardener at approx. 4 kg/m², in the color selected by the Site Management according to the Isoplam[®] color chart, incorporation into the cement matrix using an Isoplam[®] **mechanical power trowel**, followed by final smoothing.

If required, execution of control joints using Isoplam[®] **diamond blade** (in the event that polishable joints have not been previously installed), ensuring alignment with existing joints in the substrate.

Grinding and brushing (for outdoor applications) or polishing (for indoor applications).

Application of Isoplam[®] **Plam Poly Wax** or **Metallic Wax** protective treatment. Please consult the Isoplam[®] Technical Department for selection of the most suitable product.

The price includes: protection of adjacent surfaces not involved in the works, supply and delivery of materials to site, equipment, tools, and machinery necessary for execution.

For a total of m² at a unit cost of €/m² + VAT.

Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy
Tel: +39 0423 925023 - Mail: info@isoplam.it
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996
Società soggetta all'attività di direzione e coordinamento di MDF Holding