

PLAM PROFIL SANDABLE



DESCRIPTION

Plam Profil Sandable Isoplam® is a technical profile designed for the separation, closure and finishing of polished "venetian" floors in Terrazzoverlay™, Terrazzoverlay XL or Pavilux Overlay Levigato Isoplam®. It also acts as a perimeter delimitation element of the casting backgrounds of the aforementioned systems and constitutes a control and contraction joint.

It is also widely used as a separation profile, finishing, protection of external edges and decoration between floors in heterogeneous materials such as ceramic, wood, parquet, marble, granite, concrete...

It consists of a sandable bar in natural aluminium or natural brass in the shape of an L, equipped with a perforated flap that ensures its attachment to the support and subsequent covering.

FIELDS OF USE

Plam Profil Sandable Isoplam® is used in all environments, indoor and outdoor, that require good resistance to mechanical stress.

Do not use in places where aggressive substances are present and in swimming pools.

CHARACTERISTICS

<i>Material type</i>	<i>Height</i>	<i>Exposed surface</i>	<i>Bar length</i>
Natural aluminium	6 mm*	2,5 mm	2,70 m
Natural brass	20 mm*	2,5 mm	2,70 m

* other heights can be available on request based on quantity

INSTALLATION AND MAINTENANCE INSTRUCTIONS

Choose Plam Profil Sandable depending on the height of the chosen coating and the aesthetic need to be met.

Position Plam Profil Sandable according to the project and/or design of the joints, cut it to the desired size, fix it to the substrate using Plam Adesive Isoplam®, epoxy adhesive paste, pressing the perforated flap into the adhesive and let it dry.

Apply the mixture and proceed as per the technical sheet of the coating to be applied.

Glues, adhesives (even those of paper tapes), cement and its derivatives, grouts and acid pollutants, if left on the exposed surface of Plam Profil Levigabile, can corrode the metal: immediately remove these materials from the surface of the profile with a cloth moistened with water and possibly neutral detergent and dry.

IMPORTANT

All information contained in this sheet is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use. The manufacturer accepts no liability for the results of incorrect applications. This sheet replaces and cancels the previous ones. Isoplam products are intended for professional use. Isoplam Srl periodically organizes courses for its customers who request them. Anyone who uses these products without being authorized to do so does so at their own risk.