

SOLVENT RP

Retardant diluent for polyurethane resins

DESCRIPTION

Solvent RP Isoplam® is a diluent specially formulated for the dilution of Polyurethane resins to the Plam Pol Isoplam® solvent and is a solvent for cleaning the equipment used for their application.

Its retardant characteristic allows a longer duration of the processability of the resins.

USE

Solvent RP Isoplam® is ready to use.

Use as a diluent: Solvent RP should be incorporated and mixed into the mixture of the two components of Plam Pol: for the first coat add a 40-50% of Solvent RP; for the second coat add a 10-20% of Solvent RP.

Use as a solvent: remove the still fresh resin by immersing the equipment to be cleaned in Solvent RP or by rubbing with a natural fibre cloth soaked in the product.

Product residues must be disposed of in accordance with current regulations.

TECHNICAL INFORMATION

Appearance	Clear liquid
Odour	Characteristic solvent odour
Relative density	0.96 kg/L
Flash point	45.5 °C ($45.5\text{ °C} \leq T \leq 60\text{ °C}$)
Initial boiling point	145.8 °C
Vapour pressure	2 mmHg
VOC (Directive 2010/75/EU)	100.00% – 960.00 g/L
VOC (volatile carbon)	54.48% – 523.00 g/L

PACKAGING

Solvent RP Isoplam® is supplied in 5 Lt cannis.

STORAGE AND SAFETY

Store only in the original container. Store closed containers, in a well-ventilated place, away from direct sunlight. Store in a cool and well-ventilated place, away from heat sources, open flames, sparks and other sources of ignition. The product is flammable.

If adequately stored, the product is guaranteed for 24 months in the original packaging.

The date of packaging is indicated on the package (the batch number indicates, in sequence, year/week/day).



Consult the safety data sheet before use. Product intended for professional use only.

IMPORTANT:

All the information contained in this card is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use. Isoplam Srl declines all responsibility for the results of incorrect applications. It is advisable to always carry out tests on small surfaces before application. This card replaces and cancels the previous ones. The data can be changed at any time. Please also note that Isoplam products are intended for professional use and that Isoplam provides periodic training for its customers who request it. Anyone who uses these products without being authorised, does so at their own risk.